

**pco.panda**  
true sCMOS compact

up to 80%  
quantum efficiency

USB 3.1  
interface




65 mm

ultra  
compact  
design

**pco.**

true **sCMOS** compact



65 mm

**ultra  
compact  
design**

pioneer in **sCMOS** image sensor technology


## Technical Specifications

pc<sub>o</sub>.panda

<b>type of sensor</b>	customized scientific CMOS (sCMOS)
<b>resolution</b>	2048 x 2048 pixels
<b>pixelsize</b>	6.5 µm
<b>sensor format</b>	13.3 x 13.3 mm
<b>shutter mode</b>	rolling shutter
<b>fullwell capacity</b>	45 000 e <sup>-</sup>
<b>quantum efficiency</b>	up to 80 %
<b>read out noise</b>	< 2 e <sup>-</sup>
<b>dynamic range</b>	> 87 dB
<b>frame rate @ full resolution</b>	> 40 fps
<b>exposure / shutter time</b>	100 µs .. 1 s
<b>dynamic range A/D</b>	16 bit
<b>data interface</b>	USB 3.1 Gen 1 (with power via USB)
<b>power consumption</b>	< 5 W
<b>weight</b>	approx. 450 g (without lens adapter)
<b>optical input</b>	C-mount, F-mount

pc<sub>o</sub>.

# find us



## **europe**

PCO AG  
Donaupark 11  
93309 Kelheim, Germany

fon +49 (0)9441 2005 50  
fax +49 (0)9441 2005 20  
info@pco.de  
www.pco.de

## **america**

PCO-TECH Inc.  
6930 Metroplex Drive  
Romulus, Michigan 48174, USA

fon +1 (248) 276 8820  
fax +1 (248) 276 8825  
info@pco-tech.com  
www.pco-tech.com

## **asia**

PCO Imaging Asia Pte.  
3 Temasek Ave  
Centennial Tower, Level 34  
Singapore, 039190

fon +65-6549-7054  
fax +65-6549-7001  
info@pco-imaging.com  
www.pco-imaging.com

subject to changes without prior notice | ©PCO AG, Kelheim  
pco.panda.flyer | v1.02

# pco.